

Round Non-Tapered Steel

Nominal Mtg. Height (ft)	Pole Shaft Information			Pole Base Plate			Anchor Bolts	80 MPH with 1.3 Gust	90 MPH with 1.3 Gust	100 MPH with 1.3 Gust		
	Pole Specification Number	Pole O.D. (in)	Wall Thk. (in)	Thk. (in)	Sq. (in)	Bolt Circle	Dia. X Lgth. X Hook (in)	Max. EPA (ft ²)	Max. EPA (ft ²)	Max. EPA (ft ²)		
						Dia. (in)						
8	CRB411-08	4	0.120	0.5	8	8	.75 x 18 x 3	14.3	11.8	9.3		
	CRB4.511-08	4.5	0.125	0.5	8	8	.75 X 18 x 3	15.3	11.8	9.3		
	CRB511-08	5	0.120	0.5	8	8	.75 x 18 x 3	15.3	11.8	9.2		
10	CRB411-10	4	0.120	0.5	8	8	.75 X 18 x 3	11.5	8.7	6.8		
	CRB4.511-10	4.5	0.125	0.5	8	8	.75 X 18 x 3	11.5	8.7	6.8		
	CRB511-10	5	0.120	0.5	8	8	.75 X 18 x 3	11.5	8.7	6.8		
12	CRB411-12	4	0.120	0.5	8	8	.75 X 18 x 3	9	6.6	5.1		
	CRB4.511-12	4.5	0.125	0.5	8	8	.75 X 18 x 3	9	6.6	5.1		
	CRB511-12	5	0.120	0.5	8	8	.75 X 18 x 3	9	6.6	5.1		
14	CRB411-14	4	0.120	0.75	8	8	.75 X 18 x 3	8.9	6.6	4.9		
	CRB4.511-14	4.5	0.125	0.75	8	8	.75 X 18 x 3	12.2	9.1	7.3		
	CRB511-14	5	0.120	0.75	8	8	.75 X 18 x 3	15.1	11.7	9.4		
15	CRB411-15	4	0.120	0.75	8	8	.75 X 18 x 3	8	5.9	4.3		
	CRB4.511-15	4.5	0.125	0.75	8	8	.75 X 18 x 3	11.6	8	6.4		
	CRB511-15	5	0.120	0.75	8	8	.75 X 18 x 3	13.9	10.6	8.5		
16	CRB411-16	4	0.120	0.75	8	8	.75 X 18 x 3	7.1	5.2	3.6		
	CRB4.511-16	4.5	0.125	0.75	8	8	.75 X 18 x 3	9.9	7.2	5.7		
	CRB511-16	5	0.120	0.75	8	8	.75 X 18 x 3	12.3	9.5	7.6		
18	CRB411-18	4	0.120	0.75	8	8	.75 X 18 x 3	5.6	3.9	2.6		
	CRB4.511-18	4.5	0.125	0.75	8	8	.75 X 18 x 3	8	5.7	4.5		
	CRB511-18	5	0.120	0.75	8	8	.75 X 18 x 3	10.1	7.7	6.1		
20	CRB411-20	4	0.120	0.75	8	8	.75 X 18 x 3	4.4	2.9	-		
	CRB407-20	4	0.188	0.75	8	8	.75 X 18 x 3	8.4	5.9	4.3		
	CRB4.511-20	4.5	0.125	0.75	8	8	.75 X 18 x 3	6.4	4.4	3.4		
	CRB4.507-20	4.5	0.188	0.75	8	8	.75 X 18 x 3	10.7	7.8	6.1		
	CRB511-20	5	0.120	0.75	8	8	.75 X 18 x 3	8.3	6.2	4.9		
	CRB507-20	5	0.188	0.75	8	8	.75 X 18 x 3	14.9	11.5	9		
22.5	CRB411-22.5	4	0.120	0.75	8	8	.75 X 18 x 3	3	-	-		
	CRB407-22.5	4	0.188	0.75	8	8	.75 X 18 x 3	6.6	4.4	3		
	CRB4.511-22.5	4.5	0.125	0.75	8	8	.75 X 18 x 3	6.7	4.3	2.63		
	CRB4.507-22.5	4.5	0.188	0.75	8	8	.75 X 18 x 3	8.5	6	4.7		
	CRB511-22.5	5	0.120	0.75	8	8	.75 X 18 x 3	6.3	2.6	-		
	CRB507-22.5	5	0.188	0.75	8	8	.75 X 18 x 3	12.2	9.3	7.4		
25	CRB411-25	4	0.120	0.75	8	8	.75 X 18 x 3	1.9	-	-		
	CRB407-25	4	0.188	0.75	8	8	.75 X 18 x 3	5.1	3.1	1.9		
	CRB4.511-25	4.5	0.125	0.75	8	8	.75 X 18 x 3	5.1	2.9	1.3		
	CRB4.507-25	4.5	0.188	0.75	8	8	.75 X 18 x 3	6.7	4.4	3.4		
	CRB511-25	5	0.120	0.75	8	8	.75 X 18 x 3	4.6	3.2	2.5		
	CRB507-25	5	0.188	0.75	8	8	.75 X 18 x 3	10	7.4	5.9		
	CRB5.5811-25	5.58	0.134	0.75	10	10.5	.75 X 18 x 3	9.3	7.1	5.5		
CRB5.5807-25	5.58	0.188	1	10	10.5	1 X 24 X 4	15.1	11.6	9.1			
27.5	CRB4.507-27.5	4.5	0.188	1	8	8	1 X 24 X 4	5.1	3.1	2.3		
	CRB507-27.5	5	0.188	1	8	8	1 X 24 X 4	8	5.9	4.6		
	CRB5.5811-27.5	5.58	0.134	1	10	10.5	1 X 24 X 4	7.5	5.7	4.3		
	CRB5.5807-27.5	5.58	0.188	1	10	10.5	1 X 24 X 4	12.7	9.8	7.6		
	CRB6.6211-27.5	6.625	0.156	1	12	12.5	1 X 24 X 4	20.2	15.7	12.3		
30	CRB4.507-30	4.5	0.188	1	8	8	1 X 24 X 4	3.9	1.8	-		
	CRB4.503-30	4.5	0.237	1	8	8	1 X 24 X 4	6.1	3.8	2.8		
	CRB507-30	5	0.188	1	8	8	1 X 24 X 4	6.3	4.5	3.4		
	CRB5.5811-30	5.58	0.134	1	10	10.5	1 X 24 X 4	6	4.4	3.3		
	CRB5.5807-30	5.58	0.188	1	10	10.5	1 X 24 X 4	10.8	8.2	6.3		
	CRB6.6211-30	6.625	0.156	1	12	12.5	1 X 24 X 4	17.6	13.5	10.6		
35	CRB5.5807-35	5.58	0.188	1	10	10.5	1 X 24 X 4	7.5	5.5	4.1		
	CRB6.6207-35	6.625	0.188	1	12	12.5	1 X 24 X 4	12.7	9.6	7.4		
40	CRB5.5807-40	5.58	0.188	1	10	10.5	1 X 24 X 4	4.7	3.3	2.3		
	CRB6.6207-40	6.625	0.188	1	12	12.5	1 X 24 X 4	9.3	6.8	5		
	CRB6.6203-40	6.625	0.250	1	12	12.5	1 X 24 X 4	12.8	9.6	7.3		