

POLE TOP OPTIONS:
 OPEN TOP
 SIDE DRILL
 TENON
 TENON @ 90°
 OTHER

REPLACE CHART TO RIGHT
 WITH COMPLETE CHART
 FROM 8'-40' AS SHOWN ON
 ATTACHED SQUARE POLE
 EPA CHART

SEE POLE SHAFT
 INFORMATION

REINFORCED
 HANDHOLE
 WITH COVER

A

BASE DETAIL

FULL 2 PIECE BASE COVER

4 - SEE ANCHOR BOLTS
 INFORMATION

SEE POLE BASE INFORMATION

Square Non-Tapered Steel

Nominal Mtg. Height (ft)	Pole Shaft Information			Pole Base Plate			Anchor Bolts	80 MPH with	90 MPH with	100 MPH with 1.3
	Pole Specification Number	Pole O.D. (in)	Wall Thk. (in)	Thk. (in)	Sq. (in)	Bolt Circle Dia. (in)	Dia. X Lgth. X Hook (in)	Max. EPA (ft ²)	Max. EPA (ft ²)	Max. EPA (ft ²)
25	CSB88411-25	4	0.120	0.75	8	8	.75 X 18 X 3	5.4	2.8	-
	CSB88407-25	4	0.188	0.75	8	8	.75 X 18 X 3	5.9	3.4	-
	CSB88407-25A	4	0.188	1	8	8	1 X 24 X 4	11.1	7.5	5
	CSB88511-25	5	0.120	0.75	10	10.5	.75 X 18 X 3	8.1	4.8	2.4
	CSB88507-25	5	0.188	1	10	10.5	1 X 24 X 4	20.2	14.3	10.1
	CSB88607-25	6	0.188	1	12	12.5	1 X 24 X 4	24.3	17.3	12.3
27'6"	CSB88407-27.5	4	0.188	1	8	8	1 X 24 X 4	9	5.7	3.4
	CSB88511-27.5	5	0.120	1	10	10.5	1 X 24 X 4	8.4	5.3	2.7
	CSB88507-27.5	5	0.188	1	10	10.5	1 X 24 X 4	16.9	11.5	7.8
	CSB88607-27.5	6	0.188	1	12	12.5	1 X 24 X 4	20.4	14	9.5
30	CSB88407-30	4	0.188	1	8	8	1 X 24 X 4	7.1	4.1	2.3
	CSB88511-30	5	0.120	1	10	10.5	1 X 24 X 4	6.4	3.2	-
	CSB88507-30	5	0.188	1	10	10.5	1 X 24 X 4	14	9.1	5.6
	CSB88607-30	6	0.188	1	12	12.5	1 X 24 X 4	17	11.1	7
35	CSB88507-35	5	0.188	1	10	10.5	1 X 24 X 4	9.2	5	2
	CSB88607-35	6	0.188	1	12	12.5	1 X 24 X 4	11.2	6.2	2.6
	CSB88607A-35	6	0.188	1.25	12	12.5	1.25 X 44 X 4	14	8.5	4.5
	CSB88603-35	6	0.250	1.25	12	12.5	1.25 X 44 X 4	23.2	17.1	11.7
40	CSB88607-40	6	0.188	1	12	12.5	1 X 24 X 4	6.4	2	-
	CSB88607-40A	6	0.188	1.25	12	12.5	1.25 X 44 X 4	8.9	4	-
	CSB88603-40	6	0.250	1.25	12	12.5	1.25 X 44 X 4	12.6	7	2.9

CEM-TEC Corporation
 Steel Light Standards since 1974.

SQUARE POLE
 CSB SERIES